

Allround



M22M

from \$798

- **Exchangeable lens camera** for indoor/outdoor use (IP65)
- **3MEGA-resolution** (QXGA, 2048x1536 pixels)
- Exchangeable lenses from Super Wide-Angle (90°) to tele (15°); optional with C-/CS-Vario
- Color sensor 1 lux at 1/60 sec, 0.05 lux at 1 sec exposure time
- Microphone and speaker with full audio functionality (VoIP and SIP telephony with video)
- Universal wall/ceiling mount perfectly covers RJ45 outlets and conceals the cabling
- Internal DVR (up to 8 GB) possible, recording without network load

DualNight



M12D

from \$998

- **Dual camera** with brilliant image color quality during the day and highest sensitivity at night thanks to **two separate image sensors for color and B/W**, for indoor and outdoor (IP65)
- **3MEGA-resolution** (QXGA, 2048x1536 pixels)
- B/W sensor (at night or IR lighting): 0.1 lux at 1/60 sec, 0.005 lux at 1 sec exposure time
- PIR sensor for motion detection in the dark
- Microphone and speaker with full audio functionality (VoIP and SIP telephony with video)
- Integrated switch functions (1 x signal input, 1 x signal output), RS232
- Internal DVR (16 GB), recording without network load

MonoDome



D22M

from \$648

- **FixDome camera** for flexible mounting, for indoor and outdoor (IP65)
- **Optional vandalism, On-Wall and In-Ceiling sets**
- **3MEGA-resolution** (QXGA, 2048x1536 pixels)
- Exchangeable lenses from Super Wide-Angle (90°) to tele (15°)
- Color sensor 1 lux at 1/60 sec, 0.05 lux at 1 sec exposure time
- Vandalism set consists of stainless steel ring (polished, matt, powder-coated) and reinforced dome
- On-Wall set features concealed cabling, space for expansion modules (batteries, UMTS, WiFi, etc.)
- Outdoor wall mount (IP65) with space for expansion modules
- Internal DVR (16 GB), recording without network load

DualDome



D12D

from \$1198

- **DualDome camera** with **two individually positionable image sensors**, for indoor & outdoor (IP65)
- Simultaneous monitoring of different room areas using two separately directionable lenses
- **3MEGA-resolution** (QXGA, 2048x1536 pixels)
- 180° panorama
- PIR sensor for motion detection in the dark
- Microphone and speaker with full audio functionality (VoIP and SIP telephony with video)
- Integrated switch functions (2 x signal input, 2 x signal output), RS232
- Internal DVR (16 GB), recording without network load

Hemispheric



Q22M

from \$698

- **Hemispheric camera with 360° allround view** for complete room monitoring
- Without mechanically moving parts, robust and maintenance free, for indoor and outdoor (IP65)
- Digital, continuous 8x zoom and panning
- Event-controlled **360° recording**, directly in the camera with SD card support
- Alarm functions, speaker and microphone installed
- Perfect design with low installation height for in-ceiling mounting
- Compatible with all D22 accessories
- Internal DVR (16GB), recording without network load

| |
|---|
| HiRes 3 Megapixel 2048 x 1536 software zoom |
| Skyline Format free each imageformat freely definable |
| 30 Frames/s VGA (640 x 480) 10 F/s Mega |
| Virtual PTZ digital pan, tilt, zoom, |
| Backlight safe using CMOS without mechanical iris |
| Internal DVR internal via SD card, external via Network |
| Win/Lin/Mac Recording via Network on PC up to 1 Terabyte |
| microphone & speaker Audio bi-directional via IP variable framerates |
| SIP-Client with video IP-Telephony alarm notify, cam remote control |
| Video motion multiple windows precision pixel-based |
| -22°F ... +140°F Weatherproof -30° ... +60°C, IP65 no heating necessary |
| IEEE 802.3af PoE network power even in winter |
| Robust no moving parts fiber glass housing |
| MxCC Licence free Video-Management- Software |

HiRes Video Innovations

The German company MOBOTIX AG is known as the leading pioneer in network camera technology and its decentralized concept has made high-resolution video systems cost efficient.

MOBOTIX CORP • Manhattan (NY) • Phone: 888-MOBOTIX (662 6849) • us-info@mobotix.com • Made in Germany



Model: **M22M-IT-D22**
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0)
Resolution: VGA (640x480 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps
Internal DVR: ./.
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE or MX30V • via ExtIO
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS
Prices: **\$798 (MX-M22M-IT-D22)**



Model: **M22M-Sec**
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm
Resolution: 3MEGA (2048x1536 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps
Internal DVR: ./.
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE or MX30V • via ExtIO
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS
Prices: **\$998 (MX-M22M-Sec)**



Model: **M22M-Sec-Night**
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm
Resolution: MEGA (1280x960 pixels), B/W
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 0,1 lux (t=1/60sec) • 0,005 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps
Internal DVR: ./.
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE or MX30V • via ExtIO
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS
Prices: **\$998 (MX-M22M-Sec-Night)**



Model: **M22M-Sec-CSVario**
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) CS-Mount Vario 24-54 (24 bis 54mm) F 1.6-2.3
Resolution: 3MEGA (2048x1536 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps
Internal DVR: ./.
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE or MX30V • via ExtIO
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS
Prices: **\$1398 (MX-M22M-Sec-CSVario)**



NEW Internal Flash Recording

Model: **M22M-Sec-R8**
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm
Resolution: 3MEGA (2048x1536 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps
Internal DVR: 8 GB CF-card installed
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE or MX30V • via ExtIO
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS
Prices: **\$1298 (MX-M22M-Sec-R8)**



Model: **M12M-Web-D43**
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) Wide-angle only (43mm, F 2.0) no other lens available
Resolution: 3MEGA (2048x1536 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: ISDN, Ethernet 10/100 Mbps
Internal DVR: ./.
Audio/Telephony: ./.
Power Sup. • In/Out: PoE or MX30V • ./.
Software Features: Logo generator, FTP, E-Mail
Arming • Triggering: 7 day schedule • multiple events
External Storage: FTP, triggered by events/time schedule
Prices: **\$998 (MX-M12M-Web-D43)**



Model: **M12D-IT-DNight-D43N43**
Indoor/Outdoor: Dual lens outdoor, -30°...+60°C
Lenses: (eq. 35mm) 2 Wide-angle (43mm, F 2.0), DNight: automatic Day/Night switching
Resolution: 2 x VGA (je 640x480 pixels), color & B/W
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF
Sensitivity: 0,1 lux (t=1/60sec) • 0,005 lux (t=1/1sec)
Interfaces: ISDN, Ethernet 10/100 Mbps, RS232
Internal DVR: up to 16 GB with SD card
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE or MX30V • 1xIN, 1xOUT
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS
Prices: **\$1198 (MX-M12D-IT-DNight-D43N43)**



Model: **M12D-Sec-D22D135**
Indoor/Outdoor: Dual lens outdoor, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0), tele (135mm, F 2.5)
Resolution: 2 x 3MEGA (je 2048x1536 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: ISDN, Ethernet 10/100 Mbps, RS232
Internal DVR: up to 16 GB with SD card
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE or MX30V • 1xIN, 1xOUT
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS
Prices: **\$1498 (MX-M12D-Sec-D22D135)**



Model: **M12D-Sec-DNight-D43N43**
Indoor/Outdoor: Dual lens outdoor, -30°...+60°C
Lenses: (eq. 35mm) 2 Wide-angle (43mm, F 2.0), DNight: automatic Day/Night switching
Resolution: 1 x 3MEGA (2048x1536 pixels), color 1 x MEGA (1280x960 pixels), B/W
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 0,1 lux (t=1/60sec) • 0,005 lux (t=1/1sec)
Interfaces: ISDN, Ethernet 10/100 Mbps, RS232
Internal DVR: up to 16 GB with SD card
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE or MX30V • 1xIN, 1xOUT
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS
Prices: **\$1498 (MX-M12D-Sec-DNight-D43N43)**



Model: **M12D-Sec-DNight-D22N22**
Indoor/Outdoor: Dual lens outdoor, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, F 2.0), DNight: automatic Day/Night switching
Resolution: 1 x 3MEGA (2048x1536 pixels), color 1 x MEGA (1280x960 pixels), B/W
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 0,1 lux (t=1/60sec) • 0,005 lux (t=1/1sec)
Interfaces: ISDN, Ethernet 10/100 Mbps, RS232
Internal DVR: up to 16 GB with SD card
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE or MX30V • 1xIN, 1xOUT
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS
Prices: **\$1598 (MX-M12D-Sec-DNight-D22N22)**



NEW Internal Flash Recording

Model: **M12D-Sec-R8**
Indoor/Outdoor: Dual lens outdoor, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0), 43mm, 135mm
Resolution: 1 x 3MEGA (2048x1536 pixels), color 1 x MEGA (1280x960 pixels), B/W
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 0,1 lux (t=1/60sec) • 0,005 lux (t=1/1sec)
Interfaces: ISDN, Ethernet 10/100 Mbps, RS232
Internal DVR: 8 GB CF-card installed
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE or MX30V • 1xIN, 1xOUT
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS
Prices: **from \$1848 (MX-M12D-Sec-R8)**

MOBOTIX HiRes IP Cameras 2008

- 3 -



The HiRes Video Company



Model: D22Mi-Basic-D22
Indoor/Outdoor: Indoor, IP54, -30°...+50°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0)
Resolution: VGA (640x480 pixels), color
Pan/Tilt/Zoom: ./.
Frame Rate (Mono): 16 fps VGA • 16 fps CIF
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps
Internal DVR: ./.
Audio/Telephony*: ./.
Power Sup. • In/Out: PoE oder MX30V • ./.
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: ./.
External Storage: ./.
Prices: **\$648** (MX-D22Mi-Basic-D22)



Model: D22M-IT-D22
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0)
Resolution: VGA (640x480 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps, USB, ext. Audio
Internal DVR: up to 16 GB with SD card
Audio/Telephony*: bidirectional, VoIP, IP-Telephony*
Power Sup. • In/Out: PoE or MX30V • via ExtIO
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS
Prices: **\$748** (MX-D22M-IT-D22)



Model: D22M-Sec
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm
Resolution: 3MEGA (2048x1536 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps, USB, ext. Audio
Internal DVR: up to 16 GB with SD card
Audio/Telephony*: bidirectional, VoIP, IP-Telephony*
Power Sup. • In/Out: PoE or MX30V • via ExtIO
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS
Prices: **\$948** (MX-D22M-Sec)



Model: D22M-Sec-Night
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm
Resolution: MEGA (1280x960 pixels), B/W
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 0,1 lux (t=1/60sec) • 0,005 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps, USB, ext. Audio
Internal DVR: up to 16 GB with SD card
Audio/Telephony*: bidirectional, VoIP, IP-Telephony*
Power Sup. • In/Out: PoE or MX30V • via ExtIO
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS
Prices: **\$948** (MX-D22M-Sec-Night)



Model: Q22M-Basic
Indoor/Outdoor: Indoor, IP54, -30°...+50°C
Lenses: (eq. 35mm) Hemispheric (11mm, 360°, F 2.0), Super Wide Angle (22mm, 90°, F 2.0)
Resolution: VGA (640x480 pixels), color
Pan/Tilt/Zoom: digital PTZ via MxControlCenter
Frame Rate (Mono): 16 fps VGA • 16 fps CIF
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps
Internal DVR: ./.
Audio/Telephony*: ./.
Power Sup. • In/Out: PoE or MX30V
Software Features: distortion correction in MxCC, FTP, E-Mail, video alarm manag., multiview
Arming • Triggering: ./.
External Storage: ./.
Prices: **\$698** (MX-Q22Mi-Basic-D11)



Model: Q22M-Sec
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) Hemispheric (11mm, 360°, F 2.0), Super Wide Angle (22mm, 90°, F 2.0)
Resolution: 3MEGA (2048x1536 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps, USB, ext. Audio
Internal DVR: up to 16 GB with SD card
Audio/Telephony*: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE or MX30V • via ExtIO
Software Features: distortion correction in the camera, FTP, E-Mail, video alarm manag.
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS
Prices: **\$898** (MX-Q22M-Sec-D11)



Model: D12Di-IT
Indoor/Outdoor: Dual lens indoor, IP54, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0)
Resolution: 2 x VGA (je 640x480), color & B/W
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: ISDN, Ethernet 10/100 Mbps, RS232
Internal DVR: up to 16 GB with SD card
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE or MX30V • 1xIN, 1xOUT
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS
Prices: **\$1198** (MX-D12Di-IT)



Model: D12Di-Sec
Indoor/Outdoor: Dual lens indoor, IP54, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm
Resolution: 1 x 3MEGA (2048x1536 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: ISDN, Ethernet 10/100 Mbps, RS232
Internal DVR: up to 16 GB with SD card
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE or MX30V • 1xIN, 1xOUT
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS
Prices: **\$1448** (MX-D12Di-Sec)



Model: D12Di-Sec-180°
Indoor/Outdoor: Dual lens indoor, IP54, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0)
Resolution: 1 x 3MEGA (2048x1536 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: ISDN, Ethernet 10/100 Mbps, RS232
Internal DVR: up to 16 GB with SD card
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE or MX30V • 1xIN, 1xOUT
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS
Prices: **\$1448** (MX-D12Di-Sec-180°)

MxControlCenter for Windows Client:
 High performance with up to 40 smooth video streams live/stored (on a single PC), integration of analog and digital PTZ cameras with joystick control, alarm management, event search



| Lens options | L22 Day | L22 Night | L32 Day | L32 Night | L43 Day | L43 Night | L65 Day | L65 Night | L135 Day | L135 Night |
|-------------------------------|---|-----------|---------|-----------|---------|-----------|---------|-----------|----------|------------|
| | • Standard delivery (incl.) • Optional lens (excl.) | | | | | | | | | |
| M22M-IT-D22 | • | - | • | - | • | - | • | - | • | - |
| M22M-Sec | • | - | • | - | • | - | • | - | • | - |
| M22M-Sec-Night | - | • | - | • | - | • | - | • | - | • |
| M12M-Web-D43 | - | - | - | - | • | - | - | - | - | - |
| M12D-IT-DNight-D43N43 | - | - | - | - | • | • | - | - | - | - |
| M12D-Sec-D22D135 | • | - | - | - | - | - | - | - | • | - |
| M12D-Sec-DNight-D22N22 | • | • | - | - | - | - | - | - | - | - |
| M12D-Sec-DNight-D43N43 | - | - | - | - | • | • | - | - | - | - |
| D12Di-IT/D12Di-Sec | • | • | • | • | • | • | • | • | • | • |
| D22Mi-Basic-D22 | • | - | • | - | • | - | • | - | • | - |
| D22M-IT-D22 | • | - | • | - | • | - | • | - | • | - |
| D22M-IT-Night-N22 | - | • | - | • | - | • | - | • | - | • |
| D22M-Sec | • | - | • | - | • | - | • | - | • | - |
| D22M-Sec-Night | - | • | - | • | - | • | - | • | - | • |

Prices ex works Germany • Excl. VAT and country specific customs taxes • Subject to change without notice

M12/M22 Access.



Part Name: SecureFlex-Wall-/Ceiling Mount
Description:

- protected concealed cabling
- ± 90° right/left pivoting
- 70° down tilt
- covers RJ45 wall outlets
- compatible with M1/M10/M12-cameras

Prices: \$68 (MX-WH-SecureFlex)



M12/M22-Pole Mount

- 3mm stainless steel, white
- mast or pole mounting
- Pole circumference from 60 to 180mm
- 2 x metal mounting bands, fittings and grommet included

\$128 (MX-MH-SecureFlex-ESWS)



Cam-IO-PoE / AC / ACplus

- Interface for external sensors and equipment (door contact, light, etc.)
- 2xRelais-Out, 2xInput, backup, audio
- Power supply via network / 230V / 230V battery buffered

from \$398 (MX-CAMIO)

D12 Accessories



D12 Vandalism Set

- Reinforced dome (3mm Polyc.)
- Stainless steel vandalism ring (matt, polished or white, silver, black powder-coated)

\$248 (MX-D12-Vandal)



D12 Wall Mount

- Weatherproof (IP65) for D12D-Dome
- robust and UV resistant PBT-30GF
- concealed cabling
- covers RJ45 wall outlets
- possible to fit WLAN or GSM/GPRS equipment inside housing

\$148 (MX-WH-Dome)



D12 Pole Mount

- 3mm stainless steel, powder-coated
- Pole diam.: 60 to 180mm
- Incl. mounting supplies

\$148 (MX-MH-Dome-ESWS)

D22 Accessories



Part Name: D22 Vandalism Set
Description:

- Reinforced dome (3mm Polyc.)
- Stainless steel vandalism ring (matt, polished or white, silver, black powder-coated)

Prices: \$148 (MX-D22M-Vandal)



D22 On-Wall Set

- On-wall mount incl. mounting parts
- Concealed cabling
- Ø 165x37mm/6.5x1.5in
- excluding camera

\$148 (MX-D22M-OPT-AP)



D22 In-Ceiling Set

- In-ceiling set incl. mounting parts
- Easy mounting from front
- Ø 150mm/5.9in diameter
- excluding camera

\$148 (MX-D22M-OPT-IC)



D22 Wall Mount

- Weather protection (IP65) for D22
- Covers RJ45 wall outlets
- Space for expansion modules (WiFi)


\$148 (MX-D22M-OPT-WH)



D22 Pole Mount

- 3mm stainless steel, powder-coated
- Pole diam.: 60 to 180mm
- Incl. mounting supplies

\$148 (MX-D22M-OPT-MH)



Access. All Cams



Part Name: Network Power Adapter Set
Description: Power supply via network cabling
 All camera models (MX30V)

Prices: \$98 (MX-NPA-Set)



Network Power Box for 4 cameras
 Power supply for DIN rails
 All camera models (MX30V)

\$398 (MX-NPR-4)



Network Power Rack (8/20 cameras)
 Power supply via network cabling
 All camera models (MX30V)

from \$998 (MX-NPR-8/MX-NPR-20)



M12-DevKit

- M12 main board incl. sound module for connecting up to 2 cameras
- without housing for concealed installation
- housing available separately

from \$1142 (MX-M12-DevKit-Board)



ExtIO

- Each with 2 In- and Output contacts 8-24V
- Microphone with adjustable volume control, speaker, status LEDs
- USB interface
- Temperature sensor, 2 buttons

\$298 (MX-ExtIO)



L22 Super Wide Angle (90° x 67°)



L32 Wide Angle (60° x 45°)



L43 Wide Angle (45° x 34°)



L65 Tele (31° x 23°)



L135 Tele (15° x 11°)



V24-54 CSVario*



Lenses